

HAWKER® Advanced Battery Interface



HAWKER® ABI Advanced Battery Interface



- Extend asset life and increase productivity
- Reduce unplanned downtime
- Cut Total Cost of Ownership (TCO)
- Optimize battery fleet operations

The HAWKER® ABI – Advanced Battery Interface device features a lift truck-mounted remote monitor that gives drivers a live view of key battery operating conditions. The HAWKER® ABI device can read data via Bluetooth or CAN from the Battery Boss™ WC 4 (BBWC4). For HAWKER FLEX® Li³ Batteries and HAWKER FLEX® Elite Batteries, the ABI receives data directly via the Battery Management System (BMS). Regardless of communication protocol, the ABI displays a wide range of alerts, alarms and more to help optimize your battery driven operation.

By providing real-time battery information in an accessible, easy-to-read format, the HAWKER® ABI device gives operators the tools to help their operation avoid costly unplanned downtime caused by premature failures.



www.hawkerpowersource.com


1-877-7HAWKER

Power Management in the Driver's Seat

The CAN-enabled HAWKER® ABI device plays a frontline role in the transformation of battery data into actionable intelligence by communicating via Bluetooth or CAN from the BBWC, or CAN from the BMS on a FLEX® Li3 or FLEX® Elite battery. Along with our HAWKER® MOD-ifi™ smart device APP, HAWKER® chargers, and the HawkerNET™ operations management system - the HAWKER® ABI battery dashboard supports higher reliability and longer battery life.



Batter Monitoring Device



Modular Charging Technology



Smart Device Application



Battery Operations Management System

Battery Intelligence on Display

The HAWKER® ABI features a 4.3-inch (109.22 mm) touchscreen mounted on the vehicle dashboard for easy viewing and access. The display screen starts up automatically on vehicle power-up, and notifies the driver via alarms and alerts as necessary. Without having to stop the truck, drivers can review a range of essential battery operating data, including:

- Remaining work time
- Temperature
- State of Charge (SoC)
- Electrolyte levels
- Driver Recharge Notification



HAWKER® Batteries with BBWC4

Part No	Description
6LA20723-PN1H	ABI Dashboard Bluetooth Only
6LA20723-PN2H	ABI Dashboard Bluetooth or CAN
6LA20738	Mounting Bracket
6LA20737-L2	Power supply cable - 2m
6LA20737-L4	Power supply cable - 4m
6LA01159-L2	2m CAN Cable for PN2H
6LA01159-L4	4m CAN Cable for PN2H

HAWKER FLEX® Li³ and Elite Batteries

Part No	Description
6LA20723-PN3H	ABI Dashboard
6LA20738	Mounting Bracket
6LA20750-L2	Power Supply cable - 2m with Mounting Bracket
6LA20750-L4	Power Supply cable - 4m with Mounting Bracket
GL0005044-0001	HAWKER® ABI with bracket/4m cable kit
GL0004144-0001	Basic Battery Data Indicator (BDI)

Applicable to Flooded Lead Acid and TPPL batteries.



P.O. Box 808 | Ooltewah, Tennessee 37363 USA | Phone: (423) 238.5700 | www.hawkerpowersource.com

© 2024 Hawker Powersource, Inc. All rights reserved. All trademarks and logos are the property of or licensed to Hawker Powersource, Inc. and their affiliates. Subject to revisions without prior notice. E. & O.E.

AM-HABI-F Rev. AC February 2024